



SPECIFICATION

- ▼ Voltage – 3300 Volts.
- ▼ Current – 500 Amps.
- ▼ 3 Mains contact tubes.
- ▼ Weight – 8.4 kgs.
- ▼ Conductor CSA up to 185mm².


FEATURES & BENEFITS

- ▼ Crimped or grub screwed contact tubes.
- ▼ No resin required.
- ▼ Fully interchangeable with components designed to BS 3454.
- ▼ Centre pilot version available.
- ▼ Double ended contact tubes available to allow plug in contact pins.

STANDARDS & CERTIFICATION

EN IEC 60079-0: 2018, EN 60079-1: 2014

ATEX Certificate No. Sira 00ATEX1191U

 I M2 Ex db I Mb

UKEX Certificate No. Sira 21UKEX1021U


 I M2 Ex db I Mb

For more information on possible variants please contact Victor Sales:
Tel: 0191 280 8000, Email: sales@victor.co.uk



Victor

VICTOR PRODUCTS LIMITED

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk
A Federal  Signal Company

LEAFLET NO. DS005 REV 0 01/24