



PECIFICATION

- ▼ Provision of 3 contact tubes (crimped type) as standard.
- ▼ Suitable for stranded conductors, Copper or Aluminium, up to 185mm².
- ▼ Current rating – 500 Amps.
- ▼ Voltage – 3300 Volts.
- ▼ Weight – 9 kgs (unfilled) - 13kg (filled).

STANDARDS & CERTIFICATION

EN IEC 60079-0: 2018 and EN 60079-1: 2014

ATEX Certificate No. MECS 02ATEX5089U


ATEX Certificate No. MECS 02ATEX5090

(coupler pair).

UKEX Certificate No. BAS21UKEX0322U

UKEX Certificate No. BAS21UKEX0323

(coupler pair).

 I M2 Ex db I Mb

FEATURES & BENEFITS

- ▼ Compact size and weight.
- ▼ Heavy duty metal body.
- ▼ Fast make-off.
- ▼ Suitable for SWA, DWA and wire braid cables.
- ▼ Suitable for Group 1 hazardous areas.
- ▼ Suitable for the termination and connection of mains cables for deep mine, opencast and industrial environments.
- ▼ Removable pins enable connection with a mating half coupler, adaptor or other suitable equipment.
- ▼ Coupler must be solid filled after make-off – See fitting instructions.
- ▼ For unarmoured cable please see MK1 design.

For more information on possible variants please contact Victor Sales:

Tel: 0191 280 8000, Email: sales@victor.co.uk



Victor

VICTOR PRODUCTS LIMITED

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk

A Federal  Signal Company

LEAFLET NO. DS012 REV 0 02/24