



SPECIFICATION

- ▼ Provision of 3 contact tubes (crimped type) as standard.
- ▼ Suitable for stranded Copper or Aluminium conductors, up to 185mm².
- ▼ Current rating – 500 Amps.
- ▼ Voltage – 6600 Volts.
- ▼ Weight – 15kgs (unfilled) - 19kg (filled).

STANDARDS & CERTIFICATION

EN IEC 60079-0: 2018 and EN 60079-1: 2014

ATEX Certificate No. MECS 02ATEX5094U

ATEX Certificate No. MECS 02ATEX5095

(coupler pair).

UKEX Certificate No. BAS22UKEX0089U

UKEX Certificate No. BAS22UKEX0090

(coupler pair).

 I M2 Ex db I Mb

FEATURES & BENEFITS


- ▼ Compact size and weight.
- ▼ Heavy duty metal body.
- ▼ Fast make-off.
- ▼ Suitable for S.W.A, D.W.A and wire Braid cable.
- ▼ Suitable for Group 1 hazardous areas.
- ▼ Suitable for the termination and connection of mains cables for deep mine, opencast and industrial environments.
- ▼ Removable pins enable connection with a mating half coupler, adaptor or other suitable equipment.
- ▼ Coupler must be solid filled after make-off – See fitting instructions.

For more information on possible variants please contact Victor Sales:
Tel: 0191 280 8000, Email: sales@victor.co.uk



Victor

VICTOR PRODUCTS LIMITED

Unit 3A, Tyne dock East Side, Port of Tyne, South Shields NE33 5SQ United Kingdom
Tel: 0191 280 8000, Fax: 0191 280 8080 Email: sales@victor.co.uk Web: www.victor.co.uk
A Federal  Signal Company

LEAFLET NO. DS017 REV 0 03/24